



AR8 - 10.15 CMW HW
AR8 - 14.20 CTW HW


MAX bar
150÷200


MAX l/h
600÷840


kW
2.6÷5.0

AR8-10.15CMW HW



Flanged pressure unloader /
Valvola di regolazione flangiata

GENERAL FEATURES / CARATTERISTICHE GENERALI

- High pressure washer with Dual PRO Appliance system that allows to select **by-pass** or **total stop system** mode (15612) / **total stop system timed** (15613).
- Sturdy stainless steel cover
- Pressure adjustment
- Pressure gauge
- Non markin hose (10 m)
- Gun with swivel
- Idropulitrice dotata di Sistema Dual PRO Appliance integrato, con possibilità di selezione **by-pass** o **total stop system** (15612) / **total stop system temporizzato** (15613)
- Robusta copertura in acciaio inox
- Regolazione della pressione
- Manometro
- Tubo antitraccia rinforzato (10 m)
- Pistola con swivel



TECHNICAL DATA / DATI TECNICI

MODEL	AR CODE	 MAX				 MAX								 KG NET
		bar max	bar work	psi max	psi work	l/h work	gph work	hp	kW	kW work	rpm	V	Hz	kg
AR8-10.15CMW HW	15612	150	120	2175	1740	630	166	2.7	2	2.6	1450	220-240~	50	33.3
AR8-14.20CTW HW	15613	200	180	2900	2600	840	238	5.5	4	5	1450	400 3~	50	36.3

(15612) (15613)
HRC / HRC + VRZ

- Triplex pump with ceramic pistons and connecting rod system with brass pump head
- Integrated valve (15612)
- Flanged valve (15613)
- Automatic by-pass valve with pump head pressure discharge
- Induction motor with thermal protection
- Total Stop System for high pressure washer (TSS) (15612)
- Time delayed auto stop/start with stop for motor overloading (TST) (15613)

- Pompa a 3 pistoni in ceramica con sistema biella-manovella, testa pompa in ottone
- Valvola integrata (15612)
- Valvola flangiata (15613)
- Valvola di bypass automatica con azzeramento della pressione nella testa pompa
- Motore elettrico a induzione con protezione termica
- Sistema di arresto totale immediato dell'idropulitrice (TSS) (15612)
- Sistema di arresto totale temporizzato dell'idropulitrice (TST) (15613)



15612

15613

STANDARD ACCESSORIES / ACCESSORI STANDARD



code / codice	47209	47078	3082 (1504)
inlet / entrata	M22x1,5 M 14 mm	M22x1,5 M	1/4 NPT M
outlet / uscita	M22x1,5 F	1/4 NPT F	-



10 m



code / codice	5640190	51702
inlet / entrata	M22x1,5 F	-
outlet / uscita	M22x1,5 F	-

LOGISTIC DATA / DATI LOGISTICI

MODEL	PACKAGING SIZE	UNIT SIZE	KG GROSS	EURO PALLET	FULL TRUCK	20"	40"	40" HQ
	(LxWxH) mm	(LxWxH) mm	kg					
AR8-10.15CMW HW	642 x 342 x 384	562 x 314 x 363	TBC	12'	396	264	300	-
AR8-14.20CTW HW	642 x 342 x 384	562 x 314 x 363	TBC	12'	396	264	300	-

*Europallet | Floor loaded / sfuso