



AR1 - 8.17 CM
AR1 - 10.19 CMH


MAX bar
170÷190


MAX l/h
500÷600


kW
2.5÷2.7



AR1-8.17CM



AR1-10.19CMH

GENERAL FEATURES / CARATTERISTICHE GENERALI

- High pressure washer equipped with rubber wheels (Ø 200 mm), telescopic handle and hose reel (AR1-10.19CMH)
- Built-in accessory holder
- Pressure adjustment (AR1-10.19CMH)
- Pressure gauge
- Steel braided hose
- Self-priming function (SPF)
- Idropulitrice dotata di ruote (Ø 200 mm) con battistrada in gomma, manico telescopico e avvolgitubo (AR1-10.19CMH)
- Porta accessori integrato
- Regolazione della pressione (AR1-10.19CMH)
- Manometro
- Tubo rinforzato con treccia in acciaio
- Funzione autoadescente (SPF)



TECHNICAL DATA / DATI TECNICI

MODEL	AR CODE	 MAX		 MAX						 KG NET
		bar	psi	l/h	gph	kW	rpm	V	Hz	
AR1-8.17CM	15684	170	2465	500	132	2.5	2800	230	50	24.7
AR1-10.19CMH	15685	190	2600	600	159	2.7	2800	220-240~	50	25.0

HRM

- 3 Axial stainless steel pistons wobble-plate pump
- Tempered stainless steel pistons
- Brass pump head
- Integrated valve
- Automatic by-pass valve with pump head pressure discharge
- Single-phase induction motor with thermal protector
- Total Stop System for high pressure washer (TSS)
- High pressure sealing system with double seal

- Pompa a 3 pistoni assiali comandati dal piattello oscillante
- Pistoni in acciaio inox temperato
- Testa pompa in ottone
- Valvola integrata
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Motore elettrico monofase a induzione con protezione termica
- Sistema di arresto totale immediato dell'idropulitrice (TSS)
- Sistema di tenuta alta pressione con doppia guarnizione



STANDARD ACCESSORIES / ACCESSORI STANDARD



code / codice	3400810	4581720	4582260	5520540
inlet / entrata	M22x1,5 M 14 mm	M22x1,5 M	quick coupling / attacco rapido	
outlet / uscita	M22x1,5 F	quick coupling / attacco rapido		-
model / modello			AR1-8.17CM	AR1-10.19CMH



		8 m	10 m		
code / codice	4582270	5520530	3083830	4581170	4581160
inlet / entrata	quick coupling / attacco rapido		M22x1,5 F	M22x1,5 F	M22x1,5 M
outlet / uscita	-	-	M22x1,5 F	M22x1,5 F	-
model / modello	AR1-8.17CM	AR1-10.19CMH	AR1-8.17CM	AR1-10.19CMH	

LOGISTIC DATA / DATI LOGISTICI

MODEL	PACKAGING SIZE	UNIT SIZE	KG GROSS	FULL TRUCK	20"	40"	40" HQ
	(LxWxH) mm	(LxWxH) mm	kg				
AR1-8.17CM	420 x 395 x 740	449 x 388 x 895	24.2	10*	330	224~	464~
AR1-10.19CMH	420 x 395 x 770	449 x 388 x 895	28	10*	330	210~	435~

*Europallet | ~ Floor loaded / sfuso