

XW 30.15 N code 20179



Technical specifications

AR Code	20179
Version	N
Max flow (lpm)	30
Max flow (gpm)	7.92
Max Pressure (bar)	150
Max Pressure (psi)	2200
Power (Hp)	10
Power (Kw)	7.5
RPM	1450
Net weight (Kg)	16



Product details

3-piston alternating volumetric pumps for use on cleaning units and industrial systems. Can be coupled to various types of motors, directly or with flexible joint. Pump body and cover in die-cast aluminium alloy. Side cover may be blind or incorporate oil sight glass. Rear cover with oil drain outlet and sight glass. Pistons driven by crank-connecting rod mechanism. Pump shaft in pressed high-strength steel. Oversized friction bearings. Connecting rods in die-cast special low-friction zinc-aluminium alloy. One-piece ceramic pistons. Pump head in pressed brass. On request nickel-plated brass pump head. Double gasket sealing system. Intake and delivery valves have plugs for easier maintenance. (ATEX_Ex cod. 28378).

This website uses cookies to enhance the user experience. If you continue to browse this website, you accept our privacy policy.

[Privacy Policy \(/en/privacy\)](/en/privacy)

[Manage my cookies](#) [Accept all](#)

Standard accessories



F30 cod. 1545



**CR 1" 1/8 1:2
cod. 1670**



CR 1" cod. 1697



CR 1" cod. 1698



**VR 3B for XW
series cod.
21839**



**VR 3B for XW
series cod.
21840**