

Adjustable arms series EVO Ø max 3/4" – up to 30 m length

Ø max 1" – up to 20 m length



Art. nos. **9070 - 9084 - 9098**

Automatic rewind, spring-driven hose reel, **adjustable arms series EVO** with twin spring, in painted steel, suitable for hoses of max 30 m length in 3/4" and max 20 m length in 1". The hose reel is supplied without hoses and can be used with hoses for the supply of oils, diesel, compressed air and water. From the inlet swivel joint the fluid flows through an interchangeable hose connection adapter assembly on which the hose is mounted (standard version galvanized steel, available on demand also in stainless steel AISI 304 or AISI 316). Please see catalogue pages 228 and 229 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9070/HB)!



Art. no. **9777**
Pivoting wall mounting bracket for Art. no. 9098 - 9084.

Art. no. **9769**
Pivoting wall mounting bracket for Art. no. 9070.



Art. no. **9777**
Art. no. **9769**

Art. nos. **9070-9084-9098**



Art. nos. **9534 - 9570 - 9598**

Automatic rewind, spring-driven hose reel, **adjustable arms series EVO** with twin spring, in stainless steel AISI 304, suitable for hoses of max 30 m length in 3/4" and max 20 m length in 1".

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, diesel, compressed air and water. From the inlet swivel joint the fluid flows through an interchangeable hose connection adapter assembly on which the hose is mounted (standard version stainless steel AISI 304, available on demand also in stainless steel AISI 316).

Please see catalogue pages 228 and 229 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9534/HB)!



Art. no. **9770**
Pivoting wall mounting bracket for Art. no. 9598 - 9534.

Art. no. **9764**
Pivoting wall mounting bracket for Art. no. 9570.



Art. no. **9770**
Art. no. **9764**

Art. nos. **9534 9570-9598**



On demand these stainless steel hose reels can be supplied in accordance with directive ATEX 94/9/EC – group II – category 2.

Art. no.	Max working pressure	Connection threads IN - OUT	Internal Ø swivel joint	Max Ø hose	Max length hose 3/4" - 1"	Weight	Spool width	Suitable pivoting wall bracket	Included swivel joint	Dimensions (LxWxH) (mm)
9084	100 bar	1" (M) - 1" (F)	20 mm	1"	20 m - 15 m	27 kg	150 mm	9777	9969	270x590x600
9098					25 m - 18 m	30 kg	200 mm	9777	9969	320x590x700
9070					30 m - 20 m	32 kg	300 mm	9769	9969	460x590x700
9534					20 m - 15 m	27 kg	150 mm	9770	9986	270x590x600
9598					25 m - 18 m	30 kg	200 mm	9770	9986	320x590x700
9570					30 m - 20 m	32 kg	300 mm	9764	9986	460x590x700

/HB Hydraulic spring brake kit

Safety device for the controlled rewind of hoses, installable on all spring-driven hose reel models, eliminating the dangers caused by an uncontrolled rewind or a sudden release of the hose when unwinded during its use.

