



Partida Horta d'Amunt s/n · Apdo. de Correos nº 149 25600 BALAGUER (Lleida) · SPAIN E-mail: gespasa@gespasa.es http://www.gespasa.es

7 ++34 (9)73 451 072 ++34 (9)73 448 400

CGI-50 230 V Centrifugal self-priming pump



code. 02170

5 222a

52 I/min

> 230 VAC









> USE

- Centrifugal self-priming pump with JET-venturi system with high suction capacity for AdBlue/DEF even with small amounts of air-gas in the water.
- It is suitable for home applications, pressure groups, garden watering, washing, etc.
- Compact and noiseless pump with high suction power
- \bullet For suctions higher than 4 m, it is advisable to install a suction pipe higher than 1".

OPERATION

Fluid: clean water, AdBlue/DEF Minimum/maximum liquid Temperature: -5 °C / +40 °C Maximum working pressure: 3 bar Maximum suction height: 8 m

> TECHNICAL FEATURES

- Flow: 22-52 I/min
- Maximum pressure: 3 bar
- Motor: 0.37 kW 230 VAC 50 Hz \cdot single-phase \cdot self-ventilated
- IP-44 protection
- 2,800 rpm
- Consumption: 2.1 A
- LeqA(dB):72
- Inlet/Outlet connection: 1" GAS BSP
- ON/OFF Switch
- 2 m electrical cable with approved plug