

## PRO START 2824 12-24V

## cod. 829517



Battery-powered starter suitable for 12-24V starting of cars, vans, boats, agricultural vehicles, power sources etc. When connected to the cigar-lighter outlet it maintains the voltage on all circuits during battery changes and is also a 12V power source for use in emergencies. Fit with a safety switch for starting, it does not damage the electronics of the vehicle and allows for a large number of starting operations before being recharged. PRO START 2824 can be recharged using the special power supply, connected to the mains network, or using the cigar-lighter outlet of the vehicle (for the safeguard of the battery, charge for 12 hours before use, charge again after each use and every 3 months in any case). Characteristics: safety switch \* overload protection \* polarity reversal protection acoustic/luminous alarm \* high efficiency led lamp \* battery charge status led \* battery charging status led \* 2 x 12V jack sockets \* cable-holder pocket. Complete with: 230V AC 12V DC power adaptor, positive-negative cables with clamps, high efficiency lamp, double jack cable.























Norms:	LVD: EN 61558-1 EMC: EN 55014-1,2;		EMC: EN 61000-3-2,3						
CODE	<b>V</b> <sub>ph</sub> ≡	START	Ah	Аоит	A START MAX	W, JH	kg	BAR	
	V	V	Ah	A	A	mm(L,W,H)	kg		pz/pallet
829517	230 1 ph	12 24	44 22	800	2500	205 335 360	16,1	8004897837 56 7	26
pz/pallet - B									
39									